





# CERAMIC TILE SPECIFICATIONS



not to scale

	nominal dimension	actual dimension	qty / box	sq ft / box	box dimensions	box weight
2x4	2 x 4 x 3/8 in	4.4 x 9.7 x 1.3 cm	200	11.11	18.5 x 8.25 x 4.25 in	40 lbs
2x8	2 x 8 x 3/8 in	4.4 x 19.3 x 1.3 cm	150	15.75	16 x 9.25 x 6.5 in	53 lbs
4x4	4 x 4 x 3/8 in	9.7 x 9.7 x 1.3 cm	110	12.22	18 x 8 x 4.25 in	42 lbs

finish	matte: Agave, Citron, Iconic Blue, Ironwood, Linen, Pink Dahlia, Portland Grey	suggested grout line size	3/16"
	satin: Alpha White, Cosmic Black, Eucalyptus, Field Thistle, Moonlight, Pacific Blue, Sequoia, Wild Fig	installation type	grout & mortar
	gloss: Alabaster White, Ethereal Blue, Kelp Forest	placement	indoor / outdoor
		installation options	residential & commercial   commonly used for shower wall, wall, backsplash, feature walls
material	clay		
country of origin	Japan		

## Matte Finish Tile Performance

**Moh's Hardness** | ASTM C1895 - 6

**Dynamic Coefficient Of Friction (DCOF)** | ANSI A326.3 - 0.74

**Breaking Strength** | ASTM C648 - 842 lb<sub>f</sub>, average

**Absorption** | ASTM C373 - 0.2% (impervious - 0.5% or less)

## Satin Finish Tile Performance

**Moh's Hardness** | ASTM C1895 - 5

**Dynamic Coefficient Of Friction (DCOF)** | ANSI A326.3 - 0.45

**Breaking Strength** | ASTM C648 - 842 lb<sub>f</sub>, average

**Absorption** | ASTM C373 - 0.2% (impervious - 0.5% or less)

## Gloss Finish Tile Performance

**Moh's Hardness** | ASTM C1895 - 8

**Dynamic Coefficient Of Friction (DCOF)** | ANSI A326.3 - 0.3

**Breaking Strength** | ASTM C648 - 842 lb<sub>f</sub>, average

**Absorption** | ASTM C373 - 0.2% (impervious - 0.5% or less)

Third party testing conducted and results provided by SGS TEC Services in accordance with ASTM and ANSI standards

Clients are responsible for hiring a skilled installer that has experience in installing ceramic tiles. Based on the product specifications and ratings provided above, consult with a licensed contractor or installer regarding the application of these tiles in your specific project and site conditions prior to installation.

Each piece of ceramic tile is finished by hand, and subtle variations in color may occur. Clients should reference Ceramic Tile Installation Instructions for additional details.