

	nominal dimension	actual dimension	qty / box	sq ft / box	box dimensions	box weight
12x12	12 x 12 x 5/8 in	10 x 30 x 1.5 cm	10	9.69	12 x 12.5 x 7.5 in	70 lbs

finish	matte
material	cement
country of origin	Vietnam

suggested grout line size	1/16 inch		
installation type	grout & mortar		
placement	indoor / outdoor* *with the exception of freeze/thaw		
installation options	residential & commercial shower wall, shower floor, wall, floor, backsplash, feature walls		

Tile Performance

Moh's Hardness | ASTM C1895 - 7

Dynamic Coefficient Of Friction (DCOF) | ANSI A326.3 - 0.51

Breaking Strength | ASTM C648 - 600 lb_f, average

Absorption | ASTM C373 - 9.1% (non-vitreous = 7-20%) - prior to sealing

Third party testing conducted and results provided by SGS TEC Services in accordance with ASTM and ANSI standards

Clients are responsible for hiring a skilled installer that has experience in installing and sealing terrazzo tiles. Based on the product specifications and ratings provided above, consult with a licensed contractor or installer regarding the application of these tiles in your specific project and site conditions prior to installation.

Each piece of terrazzo tile is made by hand, and subtle variations in color, shape and thickness are to be expected. Clients should reference Terrazzo Tile Installation Instructions for additional details.